

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

AMENDMENTS TO THE CLAIMS

Please substitute the following claims for the pending claims with the same numbers respectively:

Claim 1 (Currently amended): A multi-optical axis photoelectric sensor comprising:

an elongate casing including an opening along a longitudinal direction;

a front cover covering the opening of said elongate casing;

a main element holder disposed within said elongate casing including a plurality of light guide housings disposed along a longitudinal axis of said main element holder, each having an optical element therein, said main element holder having a first engagement portion;

an additional element holder disposed within said elongate casing including a plurality of light guide housings disposed along a longitudinal axis of said additional element holder, each having an optical element therein, said additional element holder having a second engagement portion capable of mechanically

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

engaging and disengaging said first engagement portion of said main element holder;

wherein said main element holder and said additional element holder are disposed so that said plurality of light guide housings of said additional element holder disposed along the longitudinal axis of said main element holder, and said plurality of light guide housings of said main element holder disposed along the longitudinal axis of said additional element holder, are disposed in a line adjacent to the opening of said elongate casing when said additional element holder is engaged with said main element holder by said first and second engagement portions within said elongate casing;

wherein said second engagement portion of said additional element holder and said first engagement portion of said main element holder are engaged by relative movement of at least one of said main element holder and said additional element holder ~~perpendicular to a longitudinal axis of at least one of said main element holder and said additional element holder~~; and

wherein said first engagement portion of said main element holder is located between at least two of said plurality of light guide housings disposed ~~along the longitudinal axis of~~ on said main element holder.

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

Claims 2-5 (Cancelled):

Claim 6 (Original): A multi-optical axis photoelectric sensor according to claim 1, wherein each of said optical elements has a coupling terminal extending backwardly from a rear surface of said optical element, and said multi-optical axis photoelectric sensor further comprises:

a main circuit board disposed at a rear surface of said main element holder; and

an additional circuit board disposed at a rear surface of said additional element holder,

wherein said main circuit board and said additional circuit board are formed with holes therein and said coupling terminal of one of said optical elements is respectively disposed in one of the holes and respectively contacts at least one of said main circuit board and said additional circuit board.

Claim 7 (Original): A multi-optical axis photoelectric sensor according to claim 6, wherein said main circuit board and

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

said additional circuit board are electrically coupled to each other through a connector.

Claim 8 (Original): A multi-optical axis photoelectric sensor according to claim 1, wherein each said optical element in said main element holder and said additional element holder includes a coupling terminal extending outwardly from a side surface of said optical element, and said multi-optical axis photoelectric sensor further comprises:

a first circuit board disposed parallel to the light guide housings arranged in said main element holder; and

an additional circuit board disposed parallel to the light guide housings arranged in said additional element holder,

wherein said first circuit board and said additional circuit board include notches therein and said coupling terminal is respectively disposed in one of the notches and respectively contacts at least one of said first circuit board and said additional circuit board.

Claim 9 (Original): A multi-optical axis photoelectric sensor according to claim 8, further comprising

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

a control board including a control circuit for said multi-optical axis photoelectric sensor, said control board being disposed along a rear surface of said main element holder so that said control board is orthogonal to said first circuit board.

Claim 10 (Original): A multi-optical axis photoelectric sensor according to claim 8, wherein said first circuit board and said additional circuit board are electrically coupled to each other through a connector.

Claim 11 (Original): A multi-optical axis photoelectric sensor according to claim 9, wherein said first circuit board and said control board are electrically coupled to each other through a connector.

Claim 12 (Original): A multi-optical axis photoelectric sensor according to claim 1, wherein said optical element is a light emitting element.

Claim 13 (Original): A multi-optical axis photoelectric sensor according to claim 1, wherein said optical element is a light receiving element.

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

Claim 14 (Currently amended): A multi-optical axis
photoelectric sensor comprising:

an elongate casing including an opening along a longitudinal
direction;

a front cover covering the opening of said elongate casing;

a main element holder disposed within said elongate casing
including a plurality of light guide housings disposed along a
longitudinal axis of said main element holder, each having an
optical element therein, said light guide housings being arranged
to allow light to pass through a substantially planar surface of
said main element holder, said main element holder having a first
engagement portion;

an additional element holder disposed within said elongate
casing including a plurality of light guide housings disposed
along a longitudinal axis of said additional element holder, each
having an optical element therein, said light guide housings
being arranged to allow light to pass through a substantially
planar surface of said additional element holder, said additional
element holder having a second engagement portion capable of
mechanically engaging and disengaging said first engagement
portion of said main element holder;

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

wherein said main element holder and said additional element holder are disposed so that said substantially planar surface of said main element holder disposed along the longitudinal axis of said additional element holder, and said substantially planar surface of said additional element holder disposed along the longitudinal axis of said main element holder, are disposed in a common plane adjacent to the opening of said elongate casing when said additional element holder is engaged with said main element holder by said first and second engagement portions within said elongate casing;

wherein said second engagement portion of said additional element holder and said first engagement portion of said main element holder are engaged by relative movement of at least one of said main element holder and said additional element holder ~~perpendicular to a longitudinal axis of at least one of said main element holder and said additional element holder~~; and

wherein said first engagement portion of said main element holder is located between at least two of said plurality of light guide housings disposed ~~along the longitudinal axis of~~ on said main element holder.

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

Claim 15 (Currently amended): A multi-optical axis
photoelectric sensor comprising:

a first elongate casing including an opening along a
longitudinal direction;

a front cover covering the opening of said first elongate
casing;

a first main element holder disposed within said first
elongate casing including a plurality of light guide housings
disposed along a longitudinal axis of said first main element
holder, each having an optical projecting element therein, said
first main element holder having a first engagement portion;

a first additional element holder disposed within said first
elongate casing including a plurality of light guide housings
disposed along a longitudinal axis of said first additional
element holder, each having an optical projecting element
therein, said first additional element holder having a second
engagement portion capable of mechanically engaging and
disengaging said first engagement portion of said first main
element holder;

wherein said first main element holder and said first
additional element holder are disposed so that said plurality of
light guide housings of said first additional element holder

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

disposed along the longitudinal axis of said first main element holder, and said plurality of light guide housings of said first main element holder disposed along the longitudinal axis of said first additional element holder, are disposed in a first line adjacent to the opening of said first elongate casing when said first additional element holder is engaged with said first main element holder by said first and second engagement portions within said first elongate casing, said multi-optical axis photoelectric sensor further comprises:

wherein said second engagement portion of said first additional element holder and said first engagement portion of said first main element holder are engaged by relative movement of at least one of said first main element holder and said first additional element holder ~~perpendicular to a longitudinal axis of at least one of said first main element holder and said first additional element holder;~~

wherein said first engagement portion of said first main element holder is located between at least two said plurality of light guide housings disposed along the longitudinal axis of said first main element holder;

a second elongate casing including an opening along a longitudinal direction;

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

a second front cover covering the opening of said second elongate casing;

a second main element holder disposed within said second elongate casing including a plurality of light guide housings disposed along a longitudinal axis of said second main element holder, each having an optical receiving element therein, said second main element holder having a third engagement portion;

a second additional element holder disposed within said second elongate casing including a plurality of light guide housings disposed along a longitudinal axis of said second additional element holder, each having an optical receiving element therein, said second additional element holder having a fourth engagement portion capable of mechanically engaging and disengaging said third engagement portion of said second main element holder;

wherein said second main element holder and said second additional element holder are disposed so that said plurality of light guide housings of said second additional element holder disposed along a longitudinal axis of said second main element holder, and said plurality of light guide housings of said second main element holder disposed along a longitudinal axis of said second additional element holder, are disposed in a second line

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

adjacent to the opening of said second elongate casing when said second additional element holder is engaged with said second main element holder by said third and fourth engagement portions within said second elongate casing;

wherein said fourth engagement portion of said second additional element holder and said third engagement portion of said second main element holder are engaged by relative movement of at least one of said second main element holder and said second additional element holder ~~perpendicular to a longitudinal axis of at least one of said second main element holder and said second additional element holder;~~ and

wherein said third engagement portion of said second main element holder is located between at least two of said plurality of light guide houses disposed ~~along the longitudinal axis of~~ on said second main element holder.

Claims 16-19 (Cancelled):

Claim 20 (Previously presented): A multi-optical axis photoelectric sensor according to claim 1, wherein said second engagement portion having a cantilever portion, which is

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

projected from one end of said additional element holder, is disposed in said first engagement portion of said main element holder.

Claim 21 (Previously presented): A multi-optical axis photoelectric sensor according to claim 1, wherein said second engagement portion of said additional element holder is located between at least two of said plurality of light guide housings disposed along the longitudinal axis of said additional element holder.

Claim 22 (Previously presented): A multi-optical axis photoelectric sensor according to claim 14, wherein said second engagement portion having a cantilever portion, which is projected from one end of said additional element holder, is disposed in said first engagement portion of said main element holder.

Claim 23 (Previously presented): A multi-optical axis photoelectric sensor according to claim 14, wherein said second engagement portion of said additional element holder is located between at least two of said plurality of light guide housings

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

disposed along the longitudinal axis of said additional element holder.

Claim 24 (Previously presented): A multi-optical axis photoelectric sensor according to claim 15, wherein said second engagement portion having a cantilever portion, which is projected from one end of said first additional element holder, is disposed in said first engagement portion of said first main element holder.

Claim 25 (Previously presented): A multi-optical axis photoelectric sensor according to claim 15, wherein said second engagement portion of said first additional element holder is located between at least two of said plurality of light guide housings disposed along the longitudinal axis of said first additional element holder.

Claim 26 (Previously presented): A multi-optical axis photoelectric sensor according to claim 15, wherein said fourth engagement portion having a cantilever portion, which is projected from one end of said second additional element holder,

Application No.: 10/759,186
Amendment under 37 CFR 1.116
Reply to Office Action dated September 22, 2005
December 22, 2005

is disposed in said third engagement portion of said second main element holder.

Claim 27 (Previously presented): A multi-optical axis photoelectric sensor according to claim 15, wherein said fourth engagement portion of said second additional element holder is located between at least two of said plurality of light guide housings disposed along the longitudinal axis of said second additional element holder.